






Base model shown with added options

Add to Your Bottom Line. Reduce Your Carbon Footprint.

The Wabash Refrigerated Freight Body with EcoNex Technology is setting breakthrough performance standards. With up to 30% more thermal efficiency in a body that is up to 15% lighter, this is the stand-alone choice for bottom line growth.

Features

- Seamless exterior enables smooth, full-wall decaling
- Stainless steel rear frame provides added durability
- One Piece Header System eliminates corner caps, increasing front wall strength
- Smooth, seamless interior liner for a consistently flat and brighter food grade surface
- Engineered to significantly reduce water intrusion for longer insulation life
- EcoNex manufacturing process and operational benefits support sustainability objectives




Why EcoNex?

EcoNex is manufactured under environmentally-conscious processes and comprised of a foam-insulated core, encapsulated in a polymer fiber-reinforced shell with a protective gel coat surface. It provides unsurpassed improvement in thermal performance over conventional construction, prevents water intrusion and slows foam degradation. EcoNex ultimately extends equipment life, all while providing the benefits of its sustainable design.

Specifications

WIDTH <small>(exterior)</small>	LENGTH <small>(exterior)</small>	HEIGHT <small>(exterior)</small>		
		91"	97"	103"
96"	16'	•		
	26'		•	
102"	26'		•	•

• Available sizes limited by chassis type



One piece header system




Folding reefer steps




Stainless steel rear frame



Interior liner



E-track



Anti-skid inverted-T floor

Chassis Type	<ul style="list-style-type: none"> • Cab
Truck Body Type	<ul style="list-style-type: none"> • Insulated
Insulation	<ul style="list-style-type: none"> • 3" EcoNex - roof • 3" EcoNex - side walls • 4" EcoNex - front wall, floor
Front	<ul style="list-style-type: none"> • One-piece aluminum header • 3" radius .125 heavy duty aluminum corner post • EcoNex wall design with integral reinforcements • Refrigeration reinforcement frame
Lining	<ul style="list-style-type: none"> • Seamless, anti-microbial composite walls, roof and front wall
Rear Frame	<ul style="list-style-type: none"> • Brushed/Polished Stainless Steel • 7 ga threshold steel with bolt holes for bolt on liftgate • 12 ga header and corner posts
Rear Door	<ul style="list-style-type: none"> • Medium-temp, insulated roll-up • Safety release and lockable hasp
Floor	<ul style="list-style-type: none"> • Inverted "T" aluminum extruded non-slip floor • Four integral Kazoo drains
Subframe	<ul style="list-style-type: none"> • 6" channel longsills
Roof	<ul style="list-style-type: none"> • EcoNex roof system • Seamless construction for a smooth interior and exterior
Interior Lights	<ul style="list-style-type: none"> • LED interior motion sensor dome light – hot wired • Sealed wire harness system

Exterior Lights	<ul style="list-style-type: none"> • LED clearance lights • Existing chassis tail lights
Bumper	<ul style="list-style-type: none"> • Pooched ICC
Safety	<ul style="list-style-type: none"> • Conspicuity tape
Warranty	<ul style="list-style-type: none"> • 1-year white surface and leaks • 3-year/36,000-mile limited bulkhead-to-bumper warranty • 5-year limited structural warranty (roof, wall and floor structure) • See our warranty policy for details

Options

Front	<ul style="list-style-type: none"> • Refrigeration unit installation (single-temp) • Refrigeration unit access steps (4)
Scuff	<ul style="list-style-type: none"> • 12" corrugated aluminum
Side Doors	<ul style="list-style-type: none"> • Single-swing (36" x 73"); forward and rear opening dependent on location – limited to one curbside on selected models
Cargo Control	<ul style="list-style-type: none"> • Bonded and riveted E-track
Liftgates	<ul style="list-style-type: none"> • Contact your representative for more information